

PAINT HOSES



Part #	Size & Length	Working Pressure	Hose ID	Hose OD	Min. Bend Radius
0702-452/S	1/4" X 50ft (15mtr)	3,300psi (228bar)	0.25" (6.4mm)	0.52" (13.2mm)	4" (100mm)
0702-455/S	3/8" X 50ft (15mtr)	3,300psi (228bar)	0.375" (9.6mm)	0.69" (17.5mm)	5" (125mm)

Core : Polyamide

Reinforcement : Single braid of synthetic fibre

Cover : Blue colour, Polyurethane

Temperature : -40 to +100 deg C (not to exceed +70 deg C for air and water based fluids)



Suitable for paint spray application with increased resistance to abrasion. For use with solvents and aggressive fluids. Suitable for airless paint spray system and equipment.

Part #	Size & Length	Working Pressure	Hose ID	Hose OD	Min. Bend Radius
0702-402/S	1/4" X 50ft (15mtr)	7,540psi (520bar)	0.25" (6.4mm)	0.435" (11.0mm)	1.6" (40mm)
0702-405/S	3/8" X 50ft (15mtr)	7,200psi (500bar)	0.375" (9.6mm)	0.56" (14.2mm)	2.4" (60mm)

Core : Polyamide

Reinforcement : Single steel wire braid

Cover : Blue colour, Polyurethane

Temperature : -40 to +100 deg C (not to exceed +70 deg C for air and water based fluids)



Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Due to low permeation value of polyamide, the hose is also suitable for industrial gases. Suitable for airless paint spray system and equipment.