

G-FORCE™ II

Graco's Complete Line of Professional Gasoline Pressure Washers



PROFESSIONAL ADVANTAGES

- High performing **Honda**° **GX engines** for the toughest professional cleaning jobs: surface preparation, chemical treatment, horizontal cleaning, etc...
- Aluminium frame with dual handles delivers a lightweight and efficient design for easy transport on and off your jobsite
- Range diversity suited for your application. The right unit for the right job with our Light Duty, Contractor Duty and Heavy Duty series

G-FORCE II Extreme Reliability and PerformancePressure Washers for Professionals

The needs of your job, translated into Graco's G-FORCE II pressure washers. From occasional up to frequent and long lasting jobs, our Direct Driven and Belt Driven pressure washers provide it all. Choose the right unit for the right job.

G-FORCE™ II PRESSURE WASHERS

DIRECT DRIVE

Our compact direct driven pressure washers offer enough power and performance to tackle most cleaning and preparation jobs. Our Direct Drive range models are equipped with features that suit your occasional or typical duty applications.

BELT DRIVE

The belt drive pressure washers are Graco's top-of-the-line cold water units, designed to tackle the toughest heavy duty applications while reducing vibration and extending the life of your unit. Heavy duty engines and pumps combined with high pressure and flow provide the ideal solutions for heavy-duty applications.

Powered by Honda®

- Industrial grade engines
- Low oil level shutdown





External Unloader

- Adjusts pressure
- Protects against over heating in bypass mode
- EZ Start pressure relief



Maximize your cleaning power by selecting the tip that best matches the maximum pressure and flow



Light-Duty



Contractor-Duty



Heavy-Duty



Materials & Applications

Designed for all, fine-tuned for you and your job ... Get the G-FORCE II that suits your job requirements.

Tuno	Advantage	G-Force II	Application
Туре	Auvantage	u-roice ii	Application
LIGHT-DUTY	Light & compact with the power to perform	3325 HA-DD 3230 HA-DD	Occasional cleaning jobs by Handymen, Semi-Professionals
CONTRACTOR-DUTY	High performance & features for frequent users	4040 HG-DD 4040 HC-DD	Periodical cleaning jobs by Professional Painters and Large contractors
HEAVY-DUTY	Built to work all day, every day	4040 HG-BD 4040 HC-BD	Frequent and long lasting cleaning by Professional Painters, Large contractors







Chemical Injector Kit

Add chemicals for heavy duty cleaning jobs

Aluminium Frame

- -Up to 40% lighter
- Corrosion resistant to water and chemicals









Proven Pumps

- Professional-grade AR, General and CAT® Triplex™ plunger pumps standard across the line
- Built-in thermal sensors to prevent overheating in bypass mode

Exclusive CAT® Pump Option

- G-FORCE II 4040 HC-DD and 4040 HC-BD models
- Most durable long lasting pumps

~

Tip Selection Chart

		0°	15°	25°	40°	CHEMICAL
TIP Cutting		Chiseling	Flushing Washing		Chemical	
	USE	USE Delivers a concentrated stream that can gouge or cut. Works like a scraper when used at a 40° angle.				Low pressure nozzle for use with detergent injector.
	TYPICAL JOBS	Removes stains from concrete or other hard surfaces.	Strips paint; removes grease, mildew and stains.	Cleans dirt from outer walls, pavements, outdoor furniture, etc.	Washes vehicles, windows, aluminium cladding and other delicate surfaces.	Applies detergent, mists and rinses.




GOOD TO KNOW






Rotating and Oscillating Tips

Rotating and oscillating tips increase your cleaning power and decrease your cleaning time. They offer 0° spray impact with 25° coverage. Tips include a filter with quick connection and offer heavy-duty components for long life and reliability. They can be used on pavements, driveways, vehicle tracks, muddy areas, old peeling paints and concrete surfaces.





! TIP

Belt Drive

Belt Driven pressure washers are ideal for heavy-duty applications. The belt-pulley system provides a separate engine-pump system which reduces vibrations, RPM's and operating temperatures resulting in less pump fatigue and longer lasting performance.



G-FORCE II



	3325 HA-DD	3230 HA-DD	4040 HG-DD	4040 HC-DD	4040 HG-BD	4040 HC-BD
Part Numbers: for EURO Version (230 V)	25N638	25N639	25N681	25N682	25N683	25N684
Engine - all powered by Honda® (cm³)	GX200 (200)	GX270 (270)	GX390 (390)	GX390 (390)	GX390 (390)	GX390 (390)
Transmission	Direct	Direct	Direct	Direct	Belt	Belt
Max. Working Pressure - bar (PSI)	227 (3300)	220 (3200)	275 (4000)	275 (4000)	275 (4000)	275 (4000)
Flow - Ipm (gpm)	9.46 (2.5)	11.36 (3)	15.14 (4)	15.14 (4)	15.14 (4)	15.14 (4)
Gun - cm	91 cm + QDs	91 cm + QDs	91 cm + QDs			
Water	Cold	Cold	Cold	Cold	Cold	Cold
Pump	AR Brass Triplex	AR Brass Triplex	GP Brass Triplex	CAT® Brass Triplex	GP Brass Triplex	CAT® Brass Triplex
Adjustable unloader	Integraded	Integrated	External	External	External	External
Easy Start Pressure Relief	✓.	✓	✓	✓	✓	1
Pressure Gauge	✓.	✓	✓	✓	✓	✓
Hose	15 m + QDs	15 m + QDs	15 m + QDs			
Tips	4	4	5	5	5	5
0°- 15°- 25°- 40°	√- √- √-X	√- √- √-X	√-√-√-√	√-√-√- ✓	√-√-√-√	√-√-√-√
Chemical Tip	✓.	✓	✓	✓	✓	✓
Weight (unit only) - kg (lbs)	26.3 (58)	35.0 (77)	41.7 (92)	45.4 (100)	72.1 (132)	60.0 (132)

Accessories

Guns

TO .		
U	244785	G-FORCE gun only (345 bar)
- March	244779	G-FORCE gun 50 cm (345 bar)
	244784	G-FORCE gun 91 cm (345 bar)
	127469	G-FORCE gun 91 cm (thread) (220 bar

Extensions

16X668	G-FORCE extension 180 cm (275 bar)
116564	G-FORCE tele-extension 180 - 550 cm
	(275 bar)
16X669	G-FORCE tele-extension 180 - 730 cm
	(275 bar)
16X670	G-FORCE helt for tele-extensions

Hose Reels & Hoses

16X665	Hose reel kit, 30 m capacity (240 bar)
16X664	Hose reel kit, 30 m capacity (345 bar)
16E286	Hose 3/8" x 7.5 m Thread (240 bar)
127534	Hose 3/8" x 15 m Thread (240 bar)
244783	Hose 3/8" x 15 m Quick Disconnect (290 bar)
16X667	Hose 3/8" x 30 m Quick Disconnect (275 bar)

Wet Sandblasting Kit

	Wet ourids	usting Kit
	244766	Sandblasting kit, 380 bar
		Fittings, couplers, clamps, adapters, housing
		sealant and hose assembly (tip not included)
×	805313	Sand blasting nozzle (3325DD) (345 bar)
	805316	Sand blasting nozzle (3230DD) (345 bar)
	805321	Sand blasting nozzle (4040DD/BD)
		(345 bar)

Horizontal Surface Cleaners

16X666 Horizontal surface cleaner, 45 cm (275 bar)

Couplers & Attachments

7	16X682	G-FORCE parts box (345 bar)
J		Tips, plugs, couplers, sockets, thread-seal
7		tape and o-rings
	801568	QD coupler, 3/8" (M) x 3/8" NPT(F)
	801569	QD coupler, 3/8" (F) x 3/8" NPT(F)
0	16X679	Ball valve water shutoff (275 bar)
	19B375	Ball valve water shutoff (345 bar)
	127529	Chemical injector kit (290 bar)
	16X680	Gutter cleaning attachment (345 bar)
	801009	Coupler for wand extensions, 1/4"
	287643	Gardena® water connection adapter (brass

Fluids

246377	Pump oil, 1 litre, for triplex plunger -
	pumps only
117784	Pump oil, 0.133 liter, for radial axial -
	pumps only

Tips

198012	Rotating pressure washer tip (275 bar)
198014	Rotating pressure washer tip (360 bar)
198013	Oscillating pressure washer tip (345 bar)



ORIFICE SIZE	0°	15°	25°	40°	SET OF 4 TIPS (0°-15°- 25°- 40°)
2.7	805591	805592	805593	805594	-
3.0	805535	805536	805537	805538	244768
3.5	805539	805540	805541	805542	244769
3.7	805595	805596	805597	805598	-
4.0	805543	805544	805545	805546	800708
4.5	805547	805548	805549	805550	800709
5.0	805551	805552	805553	805554	800710
5.5	805555	805556	805557	805558	-
All tips	s are rated at 3	45 bar	Che	mical Tip	805634

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.



